

SAFETY DATA SHEET

SDS No: 10931002

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name NITROUS OXIDE- MEDICAL

Synonym(s) 10931002 - SDS NUMBER • MEDICAL NITROUS OXIDE

1.2 Uses and uses advised against

Use(s) ANAESTHETIC • MEDICAL APPLICATIONS

1.3 Details of the supplier of the product

Supplier name COREGAS PTY LTD

Address 66 Loftus Rd, Yennora, NSW, 2161, AUSTRALIA

Telephone 1800807203

Email info@coregas.com
Website http://www.coregas.com

1.4 Emergency telephone number(s)

Emergency 1800 039 008 (Australia); +61 2 9186 1132 (Backup number)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Oxidizing Gases: Category 1

Gases Under Pressure: Compressed gas

2.2 Label elements

Signal word DANGER

Pictogram(s)





Hazard statement(s)

H270 May cause or intensify fire; oxidizer.

H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

P220 Keep/Store away from clothing/incompatible materials/combustible materials.

P244 Keep reduction valves free from grease and oil.

Response statement(s)

P370 + P376 In case of fire: Stop leak if safe to do so.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.

coregas 🧐

SDS Date: 24 Aug 2016

Version No: 3.1

2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
NITROUS OXIDE	10024-97-2	233-032-0	>99.5%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate

for 15 minutes. Seek medical attention.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not

breathing. Give oxygen if available.

Skin Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15

minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for

15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.

Ingestion Ingestion is not considered a potential route of exposure.

First aid facilities No information provided.

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Direct contact with the liquefied material or escaping compressed gas may cause cold burns similar to frostbite injury.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable - oxidising agent. Supports combustion and may cause fire/explosion in contact with incompatible substances, strong acids, reducing agents, combustibles and flammables.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.

5.4 Hazchem code

2P

2 Fine Water Spray.

P Risk of violent reaction or explosion. Wear liquid-tight chemical protective clothing and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.



SDS Date: 24 Aug 2016

Page 2 of 7 Version No: 3.1

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near sources of ignition or incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
ingredient		ppm	mg/m³	ppm	mg/m³
Nitrous oxide	SWA (AUS)	25	45		

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Wear safety glasses.

Hands Wear leather or insulated gloves.

Body Wear safety boots.

Respiratory Where an inhalation risk exists, wear a Type NO (Nitrogen Oxides) respirator. At high vapour levels, wear

Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

AppearanceCOLOURLESS GASOdourSWEET ODOURFlammabilityNON FLAMMABLEFlash pointNOT RELEVANT

Boiling point -90.8°C

Melting point
Evaporation rate
pH
NOT AVAILABLE
NOT APPLICABLE
NOT APPLICABLE
NOT AVAILABLE

coregas (S

SDS Date: 24 Aug 2016

Page 3 of 7 Version No: 3.1

9.1 Information on basic physical and chemical properties

NOT APPLICABLE Specific gravity Solubility (water) SOLUBLE **NOT AVAILABLE** Vapour pressure **NOT RELEVANT Upper explosion limit NOT RELEVANT** Lower explosion limit Partition coefficient NOT AVAILABLE **Autoignition temperature** NOT AVAILABLE **Decomposition temperature NOT AVAILABLE** NOT AVAILABLE Viscosity **NOT AVAILABLE Explosive properties**

9.2 Other information

Oxidising properties
Odour threshold

% Volatiles 100%

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with powerful reducing agents such as phosphine, stannous chloride and hydrogen.

OXIDISING GAS

NOT AVAILABLE

10.6 Hazardous decomposition products

May evolve nitrogen oxides when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Information available for the product:

Based on available data, the classification criteria are not met. Nitrous oxide passes into all gas containing spaces in the body faster than nitrogen passes out, thus it should not be used with any condition where its expansion might be dangerous. May induce vomiting in susceptible individuals.

Information available for the ingredient(s):

Ingredient	Oral Toxicity	Dermal Toxicity	Inhalation Toxicity
	(LD50)	(LD50)	(LC50)
NITROUS OXIDE			1068 mg/m³ (rat)

Skin Not classified as a skin irritant. Contact with the liquefied material or escaping compressed gas may cause

frostbite injury.

Eye Not classified as an eye irritant. Contact with the liquefied material or escaping compressed gas may cause

frostbite injury.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen.

Reproductive May cause reproductive toxicity in humans. Reduced fertility in healthcare personnel has been reported

where they have been repeatedly exposed to levels of nitrous oxide above the specified occupational exposure limits in inadequately ventilated rooms. There is no documented evidence to confirm or exclude the existence of any causal connection between these cases and exposure to nitrous oxide. The substance may

have effects on the bone marrow and peripheral nervous system.

STOT – single exposure

Asphyxiant - anaesthetic. May have short term effects on the central nervous system, including drowsiness,

dizziness, euphoria and anxiolytic and analgesic effects.

SDS Date: 24 Aug 2016 Page 4 of 7 Version No: 3.1



STOT - repeated

exposure

Chronic exposure to nitrous oxide can result in some symptoms of pernicious anaemia: Megaloblastic bone-marrow depression or peripheral and central neuropathy (tingling, numbness, impairment of

equilibrium, difficulty in thinking clearly).

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

ATMOSPHERE: Nitrous oxide is toxic and is considered an air pollutant. Fairly stable in the atmosphere. May be toxic to terrestrial animals. SOIL: Due to its very low boiling point it is expected to quickly evaporate if released on soil. WATER: May dissolve in water, although evaporation will be a major removal factor.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE





	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1070	1070	1070
14.2 Proper Shipping Name	NITROUS OXIDE	NITROUS OXIDE	NITROUS OXIDE
14.3 Transport Hazard Classes	2.2, 5.1	2.2, 5.1	2.2, 5.1
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

 Hazchem code
 2P

 GTEPG
 2C8

 EMS
 F-C, S-W

Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which

affect gas storage and transport.

15. REGULATORY INFORMATION



SDS Date: 24 Aug 2016

Version No: 3.1

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 4 (S4) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes None allocated.

Risk phrases None allocated.

Safety phrases None allocated.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average



SDS Date: 24 Aug 2016 Version No: 3.1

Page 6 of 7

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.

[End of SDS]



SDS Date: 24 Aug 2016

Version No: 3.1